

RECEIVED  
CENTRAL FAX CENTER  
APR 30 2009

App. Serial No.: 09/051,263

Atty. Docket No.: 0081-012

IN THE CLAIMS

Please amend the claims as follows:

1-44. (canceled)

45. (previously presented) A microprocessor system, comprising:

- a microprocessing unit (MPU);
- an input-output processor (IOP);
- a global memory unit coupled to said MPU and to said IOP;
- a direct memory access controller (DMAC);
- an interrupt controller (INTC);
- a programmable memory interface (MIF);
- an external CMOS oscillator, operating in conjunction with a clock multiplier;
- a plurality of bit inputs; and
- a plurality of bit outputs.

46. (previously presented) The microprocessor system of claim 45, wherein:

- a frequency of said oscillator is quadrupled internally to operate said MPU and said IOP.

47. (previously presented) The microprocessor system of claim 45, wherein:

- said microprocessor system utilizes a phase locked loop circuit.

48. (previously presented) The microprocessor system of claim 45, wherein:

- said MPU retrieves up to four instructions from memory for each instruction fetch or pre-fetch.

49. (previously presented) The microprocessor system of claim 45, wherein:

- said MPU fetches multiple sequential instructions from said global memory unit in parallel, and said global memory unit supplies said multiple sequential instructions to said MPU during a single memory cycle.

App. Serial No.: 09/051,263

Atty. Docket No.: 0081-012

50. (previously presented) The microprocessor system of claim 45, wherein:  
said MPU further comprises an arithmetic logic unit (ALU) that is used for data operations and for branch address calculations.
51. (previously presented) The microprocessor system of claim 45, wherein:  
said MPU further comprises an arithmetic logic unit (ALU), and a first push down stack with a top item register and a next item register, connected to provide inputs to said ALU, an output of said ALU being connected to said top item register.
52. (previously presented) The microprocessor system of claim 45, wherein:  
said MPU comprises a zero-operand dual-stack architecture.
53. (previously presented) The microprocessor system of claim 52, wherein:  
said dual-stack architecture is cached on chip and automatically spills to and refills from external memory.
54. (previously presented) The microprocessor system of claim 45, wherein:  
said MPU comprises a plurality of global data registers and a plurality of local registers.
55. (previously presented) The microprocessor system of claim 45, wherein:  
said global memory unit is shared by said MPU, said IOP, and said MIF.
56. (previously presented) The microprocessor system of claim 45, wherein:  
said global memory unit is used for data storage and control communication with said DMAC and said IOP.
57. (previously presented) The microprocessor system of claim 45, wherein:  
said global memory unit is used by said IOP for transfer information, loop counts, and delay counts.

App. Serial No.: 09/051,263

Atty. Docket No.: 0081-012

58. (previously presented) The microprocessor system of claim 45, wherein:  
said MIF is shared by said IOP, said MPU, said DMAC, said plurality of bit outputs, and  
said plurality of bit inputs.
59. (previously presented) The microprocessor system of claim 45, wherein:  
bus transaction requests are arbitrated and prioritized by said MIF.
60. (previously presented) The microprocessor system of claim 45, wherein:  
said INTC is shared by said plurality of bit inputs, said IOP, and said DMAC.
61. (previously presented) The microprocessor system of claim 45, wherein:  
said global memory unit comprises a plurality of global registers.
62. (previously presented) The microprocessor system of claim 61, wherein:  
said plurality of global registers are used for operand storage for said MPU, and for data  
storage for said IOP.
- 63-76. (canceled)